

**Amendments to the Claims:**

Please amend claims 1 and 33 as follows. This following list of claims is intended to replace all other lists of claims.

1. (Currently Amended) A single use processing substrate, comprising;  
a first ~~cut-resistant~~ layer having a first surface area and including a cellulosic ply and a thermoplastic material ply; and  
a second layer having a second surface area and including a cellulosic ply and a thermoplastic material ply, wherein the first layer is secured to the second layer such that a portion of the second surface area is laterally disposed outside of the first surface area and wherein the portion of the second surface area includes sections of the thermoplastic ply and the cellulosic ply.
2. (Previously Presented) The single use processing substrate of claim 1, wherein the first layer cellulosic ply is disposed below the first layer thermoplastic material ply.
3. (Previously Presented) The single use processing substrate of claim 2, wherein the first layer thermoplastic material ply is extrusion coated onto the first layer cellulosic ply.
4. (Previously Presented) The single use processing substrate of claim 1, wherein the second layer cellulosic ply is disposed above the second layer thermoplastic material ply.
5. (Previously Presented) The single use processing substrate of claim 4, wherein the second layer thermoplastic material ply is extrusion coated onto the second layer cellulosic ply.
6. (Previously Presented) The single use processing substrate of claim 1, wherein the thickness of the first layer cellulosic ply is between about 2 to about 6 mils.

7. (Previously Presented) The single use processing substrate of claim 1, wherein the thickness of the second layer cellulosic ply is between about 2 to about 6 mils.

8. (Original) The single use processing substrate of claim 1, wherein the thickness of the first layer thermoplastic ply is about 5 mils.

9. (Original) The single use processing substrate of claim 1, wherein the thickness of the second layer thermoplastic ply is about 3.5 mils.

10. (Previously Presented) The single use processing substrate of claim 1, wherein the first layer thermoplastic ply and the first layer cellulosic ply include a plurality of apertures therein.

11. (Original) The single use processing substrate of claim 10, wherein the apertures are created by perforating.

12. (Original) The single use processing substrate of claim 10, wherein the apertures are created by punching.

13. (Previously Presented) The single use processing substrate of claim 10, wherein the first layer thermoplastic ply and the first layer cellulosic ply contain an average of 5.52 apertures per square inch.

14. (Previously Presented) The single use processing substrate of claim 10, wherein the apertures are substantially circular.

15. (Original) The single use processing substrate of claim 14, wherein the apertures have a diameter of about 0.08 inches.

16. (Original) The single use processing substrate of claim 10, wherein the apertures are regularly spaced.

17. (Original) The single use processing substrate of claim 16, wherein a spacing between apertures is created in the x-direction by 0.279 inches and in the y-direction by 0.165 inches.

18. (Previously Presented) The single use processing substrate of claim 17, wherein the spacing between apertures creates a zigzag pattern in the first layer thermoplastic ply and the first layer cellulosic ply.

19. (Original) The single use processing substrate of claim 1, wherein the first layer thermoplastic ply and the second layer thermoplastic ply includes a resin comprising metallocene polypropylene.

20. (Original) The single use processing substrate of claim 19, wherein the metallocene polypropylene comprises a copolymer of propylene and ethylene.

21. (Original) The single use processing substrate of claim 20, wherein the resin further includes a talc additive.

22. (Original) The single use processing substrate of claim 21, wherein the talc additive is present in an amount less than about 10 percent by weight of the resin.

23. (Original) The single use processing substrate of claim 22, wherein the resin further includes calcium, magnesium or zinc stearate.

24. (Original) The single use processing substrate of claim 23, wherein the resin further includes at least one antioxidant.

25. (Original) The single use processing substrate of claim 1, wherein the first layer is substantially centered in the second surface area in at least one direction.

26. (Original) The single use processing substrate of claim 1, wherein the first layer is substantially centered in the second surface area in both directions.

27. (Previously Presented) The single use processing substrate of claim 1, wherein the processing substrate is embossed.

28. (Original) The single use processing substrate of claim 1, wherein the first layer has dimensions of about 9.75 inches by about 7.688 inches.

29. (Original) The single use processing substrate of claim 1, wherein the second layer has dimensions of about 11.75 inches by about 9.688 inches.

30. (Original) The single use processing substrate of claim 1, wherein the first layer is secured to the second layer by adhesive.

31. (Original) The single use processing substrate of claim 30, wherein the adhesive is ethyl vinyl acetate.

32. (Original) The single use processing substrate of claim 30, wherein the adhesive is in a pattern of parallel stripes.

33. (Currently Amended) A single use processing substrate, comprising;  
a first ~~cut-resistant~~ layer having a first surface area and including a ply of tissue disposed below a ply of thermoplastic material; and

an unfolded second layer having a second surface area and including a ply of tissue disposed above a ply of thermoplastic material, wherein the first layer is secured to and substantially centered on the second layer in at least one dimension such that a portion of the second surface area is laterally disposed outside of the first surface area and wherein the portion of the second surface area includes sections of the thermoplastic ply and the tissue ply.

34. (Original) The single use processing substrate of claim 33, wherein the first layer tissue ply is disposed below the first layer thermoplastic material ply.

35. (Original) The single use processing substrate of claim 33, wherein the first layer thermoplastic material ply is extrusion coated onto the first layer tissue ply.

36. (Original) The single use processing substrate of claim 33, wherein the second layer tissue ply is disposed above the second layer thermoplastic material ply.

37. (Original) The single use processing substrate of claim 36, wherein the second layer thermoplastic material ply is extrusion coated onto the second layer tissue ply.

38. (Original) The single use processing substrate of claim 33, wherein the thickness of the first layer tissue ply is between about 2 to about 6 mils.

39. (Original) The single use processing substrate of claim 33, wherein the thickness of the second layer tissue ply is between about 2 to about 6 mils.

40. (Original) The single use processing substrate of claim 33, wherein the thickness of the first layer thermoplastic ply is about 5 mils.

41. (Original) The single use processing substrate of claim 33, wherein the thickness of the second layer thermoplastic ply is about 3.5 mils.

42. (Original) The single use processing substrate of claim 33, wherein the first layer thermoplastic ply and the first layer tissue ply include a plurality of apertures therein.

43. (Original) The single use processing substrate of claim 42, wherein the apertures are created by perforating.

44. (Original) The single use processing substrate of claim 42, wherein the apertures are created by punching.

45. (Original) The single use processing substrate of claim 42, wherein the first layer thermoplastic ply and the first layer tissue ply contain an average of 5.52 apertures per square inch.

46. (Previously Presented) The single use processing substrate of claim 42, wherein the apertures are substantially circular.

47. (Original) The single use processing substrate of claim 46, wherein the apertures have a diameter of about 0.08 inches.

48. (Original) The single use processing substrate of claim 41, wherein the apertures are regularly spaced.

49. (Original) The single use processing substrate of claim 48, wherein a spacing between apertures is created in the x-direction by 0.279 inches and in the y-direction by 0.165 inches.

50. (Original) The single use processing substrate of claim 49, wherein the spacing between apertures creates a zigzag pattern in the first layer thermoplastic ply and the first layer tissue ply.

51. (Original) The single use processing substrate of claim 33, wherein the first layer thermoplastic ply and the second layer thermoplastic ply includes a resin comprising metallocene polypropylene.

52. (Original) The single use processing substrate of claim 51, wherein the metallocene polypropylene comprises a copolymer of propylene and ethylene.

53. (Original) The single use processing substrate of claim 52, wherein the resin further includes a talc additive.

54. (Original) The single use processing substrate of claim 53, wherein the talc additive is present in an amount less than about 10 percent by weight of the resin.

55. (Original) The single use processing substrate of claim 54, wherein the resin further includes calcium, magnesium or zinc stearate.

56. (Original) The single use processing substrate of claim 55, wherein the resin further includes at least one antioxidant.

57. (Original) The single use processing substrate of claim 33, wherein the first layer is substantially centered in the second surface area in both dimensions.

58. (Original) The single use processing substrate of claim 33, wherein the first surface area and the portion of the second surface area laterally disposed outside of the first surface area are embossed.

59. (Original) The single use processing substrate of claim 33, wherein the first layer has dimensions of about 9.75 inches by about 7.688 inches.

60. (Original) The single use processing substrate of claim 33, wherein the second layer has dimensions of about 11.75 inches by about 9.688 inches.

61. (Original) The single use processing substrate of claim 33, wherein the first layer is secured to the second layer by adhesive.

62. (Original) The single use processing substrate of claim 61, wherein the adhesive is ethyl vinyl acetate.

63. (Original) The single use processing substrate of claim 61, wherein the adhesive is in a pattern of parallel stripes.

64. (Previously Presented) The single use processing substrate of claim 30, wherein the adhesive is applied in interrupted patterns.

65. (Previously Presented) The single use processing substrate of claim 64, wherein the adhesive is applied as a series of spaced spots.

66. (Previously Presented) The single use processing substrate of claim 30, wherein the adhesive is applied in a continuous pattern.

67. (Previously Presented) The single use processing substrate of claim 61, wherein the adhesive is applied in interrupted patterns.

68. (Previously Presented) The single use processing substrate of claim 67, wherein the adhesive is applied as a series of spaced spots.

69. (Previously Presented) The single use processing substrate of claim 61, wherein the adhesive is applied in a continuous pattern.

70. (Previously Presented) A processing substrate, comprising:  
a cut resistant portion having a first surface area;  
an absorbent portion disposed adjacent the cut resistant portion and having a second surface area; and  
a barrier portion disposed adjacent the absorbent portion;  
wherein the cut resistant portion, the absorbent portion, and the barrier portion are secured to one another such that a section of the second surface area is laterally disposed outside of the first surface area and wherein the cut resistant portion includes a plurality of apertures therein.



71. (Canceled)

72. (Previously Presented) The processing substrate of claim ~~71~~ 70, wherein the apertures are created by perforating.

73. (Previously Presented) The processing substrate of claim ~~71~~ 70, wherein the apertures are created by punching.

74. (Previously Presented) The processing substrate of claim 70, wherein the cut resistant portion includes a resin comprising metallocene polypropylene.

75. (Previously Presented) The processing substrate of claim 74, wherein the barrier portion includes a resin comprising metallocene polypropylene.

76. (Previously Presented) The processing substrate of claim 75, wherein the metallocene polypropylene comprises a copolymer of propylene and ethylene.

77. (Previously Presented) The single use processing substrate of claim 70, wherein the barrier layer has a third surface area equal to the second surface area.

78. (Previously Presented) The single use processing substrate of claim 1, wherein the thickness of the second layer thermoplastic ply is about 1 mil.

79. (Previously Presented) The single use processing substrate of claim 1, wherein the first layer has dimensions of about 9.75 inches by about 14 inches.

80. (Previously Presented) The single use processing substrate of claim 1, wherein the second layer has dimensions of about 11.75 inches by about 16 inches.

81. (Previously Presented) The single use processing substrate of claim 33, wherein the thickness of the second layer thermoplastic ply is about 1 mil.

82. (Previously Presented) The single use processing substrate of claim 33, wherein the first layer has dimensions of about 9.75 inches by about 14 inches.

83. (Previously Presented) The single use processing substrate of claim 33, wherein the second layer has dimensions of about 11.75 inches by about 16 inches.